



Website



VR Panorama



Catalog



DRYER
WASHING
MACHINE

INDUSTRIAL
AIR COOLER



Baoerma Electrical Group Co.,Ltd.

Add: No.789 Xintang Road, Fuhai Town, Cixi City , Ningbo ,
Zhejiang ,315332,China

Tel: +86-574-58582078 Fax: +86-574-63563187
E-mail:salea@baoerma.com http://www.baoerma.com

The company keeps the rights to alter the product design and specification. If there is any change, advance notice won't be given then.
If there is slight difference between catalogue and actual product, please take actual product as criterion. All the data have been carefully checked.
If there is any error in printing, the company holds final explanation rights.



PROFILE OF COMPANY

BAOERMA Electrical Group Co., Ltd. has been established in 1994. Its predecessor is Ningbo BAOERMA Electrical Co., Ltd. It mainly manufactures washing machine, electric fan, air-conditioner fan, heater series etc. The company integrates the product research, development, manufacture, part supply, international trade, market sales, service tracking into one. It endeavors to be an excellent electric appliance supplier in the world. The company is located in Fuhai Town, Cixi, Ningbo City, Zhejiang Province, China. Fuhai Town has been reputed as "One of Three Famous Manufacture Bases of Small Electric Appliance in China", "The Town of Electric Appliance", "Hometown of Flowers & Plants". It is one of the well-known leading enterprises of small electric appliance in Cixi, Ningbo, Zhejiang, China.

Over ten years, independent innovation concept is deeply implanted in the minds of "BAOERMA people". The famous Chinese trademark of "BAOERMA" electric appliance is endowed with infinite brand glamour by the excellent pioneering group, long history of professional electric appliance manufacture, advanced industrial design idea, high quality products, perfect after-sale service.

BAOERMA creates a famous brand by fine quality, opens up a big market by famous brand. ISO9001: 2008 Quality Supervision System Certification, China Compulsory Certification, CE; GS; EMC; CB International Certifications etc. symbolize the trustworthy product quality of "BAOERMA" electric appliance. The product sales networks are wide-spreading in over 20 domestic provinces and cities. BAOERMA successfully explores the international markets such as Europe, Japan, Korea, the Middle East, Southeast Asia, America etc. It furthermore witnesses that BAOERMA people will never cease their advancing steps towards their ambitious objectives.

"Developing & innovative, credit-centered" is the corporate spirits of BAOERMA Electrical.

"Quality innovation, quality first" is the quality principle of BAOERMA Electrical.

"Nothing largest, only better" is the unremitting pursuit of BAOERMA Electrical.

BAOERMA is always advancing forward!

BAOERMA Electrical will always boldly advance forward to every corner of the world!



CB CE K Erp RoHS



COMPANY ENVIRONMENT



BAOERMA 宝尔玛®

Administrative area



Sample room



Workshop





FRONT - LOADING DRYER



Front-loading dryer

4.0KG



4.0KG



GDZ40-188G (Electronic)

Specification

Heating method	PTC
Product size(mm)	480X400X560
Packing size(mm)	536X470X595
N.W.(kg)	14.5
G.W.(kg)	16.5
Drum volume(l)	36
Dryer power(w)	800W
Timer(min)	180
40'HQ(pcs)	440

Function

- Air vented
- Touch control panel
- 180Mins dry timer
- Adjustable temperature from 0-60 degree
- UV sterilization disinfection (option)
- Intelligent drying
- PTC dryer

GDZ40-168E (Mechanical)

Specification

Heating method	PTC
Product size(mm)	480X400X560
Packing size(mm)	536X470X595
N.W.(kg)	14.5
G.W.(kg)	16.5
Drum volume(l)	36
Dryer power(w)	800W
Timer(min)	180
40'HQ(pcs)	440

Function

- Air vented
- Mechanical control panel
- 180Mins dry timer
- 80Mins Cold air care function
- PTC dryer

Front-loading dryer

4.0KG



GDZ40-288G (Electronic)

Specification

Heating method	PTC
Product size(mm)	480X400X560
Packing size(mm)	536X470X595
N.W.(kg)	14.5
G.W.(kg)	16.5
Drum volume(l)	36
Dryer power(w)	800W
Timer(min)	180
40'HQ(pcs)	440

Function

- Air vented
- Touch control panel
- 180Mins dry timer
- Adjustable temperature from 0-60 degree
- UV sterilization disinfection (option)
- Intelligent drying
- PTC dryer

4.0KG



GDZ40-368E (Mechanical)

Specification

Heating method	PTC
Product size(mm)	480X400X560
Packing size(mm)	536X470X595
N.W.(kg)	14.5
G.W.(kg)	16.5
Drum volume(l)	36
Dryer power(w)	800W
Timer(min)	180
40'HQ(pcs)	440

Function

- Air vented
- Mechanical control panel
- 180Mins dry timer
- 80Mins Cold air care function
- PTC dryer

Front-loading dryer

4.0KG



GDZ40-388G (Electronic)

Specification

Heating method	PTC
Product size(mm)	480X400X560
Packing size(mm)	536X470X595
N.W.(kg)	14.5
G.W.(kg)	16.5
Drum volume(l)	36
Dryer power(w)	800W
Timer(min)	180
40'HQ(pcs)	440

Function

- Air vented
- Touch control panel
- 180Mins dry timer
- Adjustable temperature from 0-60 degree
- UV sterilization disinfection (option)
- Intelligent drying
- PTC dryer

4.0KG



GDZ40-398G (Electronic)

Specification

Heating method	PTC
Product size(mm)	480X400X560
Packing size(mm)	536X470X595
N.W.(kg)	14.5
G.W.(kg)	16.5
Drum volume(l)	36
Dryer power(w)	800W
Timer(min)	180
40'HQ(pcs)	440

Function

- Air vented
- Touch control panel
- 180Mins dry timer
- Adjustable temperature from 0-60 degree
- UV sterilization disinfection (option)
- Intelligent drying
- PTC dryer

Front-loading dryer

4.0KG



GDZ40-468E (Mechanica)

Specification

Heating method	PTC
Product size(mm)	480X400X560
Packing size(mm)	536X470X595
N.W.(kg)	14.5
G.W.(kg)	16.5
Drum volume(l)	36
Dryer power(w)	800W
Timer(min)	180
40'HQ(pcs)	440

Function

- Air vented
- Mechanical control panel
- 180Mins dry timer
- 80Mins Cold air care function
- PTC dryer

4.0KG



GDZ40-488G (Electronic)

Specification

Heating method	PTC
Product size(mm)	480X400X560
Packing size(mm)	536X470X595
N.W.(kg)	14.5
G.W.(kg)	16.5
Drum volume(l)	36
Dryer power(w)	800W
Timer(min)	180
40'HQ(pcs)	440

Function

- Air vented
- Touch control panel
- 180Mins dry timer
- Adjustable temperature from 0-60 degree
- UV sterilization disinfection (option)
- Intelligent drying
- PTC dryer

Front-loading dryer

4.0KG



GDZ40-378E (Mechanica)

Specification

Heating method	PTC
Product size(mm)	480X400X560
Packing size(mm)	536X470X595
N.W.(kg)	14.5
G.W.(kg)	16.5
Drum volume(l)	36
Dryer power(w)	800W
Timer(min)	180
40'HQ(pcs)	440

Function

- Air vented
- Mechanical control panel
- 180Mins dry timer
- 80Mins Cold air care function
- PTC dryer

4.0KG



GDZ40-478E (Mechanica)

Specification

Heating method	PTC
Product size(mm)	480X400X560
Packing size(mm)	536X470X595
N.W.(kg)	14.5
G.W.(kg)	16.5
Drum volume(l)	36
Dryer power(w)	800W
Timer(min)	180
40'HQ(pcs)	440

Function

- Air vented
- Mechanical control panel
- 180Mins dry timer
- 80Mins Cold air care function
- PTC dryer

Front-loading dryer

4.0KG



GDZ40-498G (Electronic)

Specification

Heating method	PTC
Product size(mm)	480X400X560
Packing size(mm)	536X470X595
N.W.(kg)	14.5
G.W.(kg)	16.5
Drum volume(l)	36
Dryer power(w)	800W
Timer(min)	180
40'HQ(pcs)	440

Function

- Air vented
- Touch control panel
- 180Mins dry timer
- Adjustable temperature from 0-60 degree
- UV sterilization disinfection (option)
- Intelligent drying
- PTC dryer



Rack (Option)



Back exhaust Vent

Mini Auto Washing Machine

1.0KG



XQB10-788G

Specification

Product size(mm)	345X345X400
Packing size(mm)	400X400X450
N.W.(kg)	9.0
G.W.(kg)	10.0
40'HQ(pcs)	900

Function

- High temp wash
- PTC dryer
- Stainless steel interior drum and washing wheel
- 10 Wash program options
- Child lock



4.5KG



XQB45-688G

Specification

Product size(mm)	527X483X696
Packing size(mm)	535X495X715
N.W.(kg)	16
G.W.(kg)	17
Max Water level(l)	25
40'HQ(pcs)	330



Stainless steel bucket
+
Stainless steel impeller



PTC dryer

Function

- Blue light sterilization
- High power air drying function
- Plastic interior tub and washing wheel
- 24delay hours start, Auto shut off
- 10 Wash program options
- Child lock
- 6 Water level options

Mini Auto Washing Machine

3.0KG



XQB30-688G

Specification

Product size(mm)	345X395X610
Packing size(mm)	410X455X650
N.W.(kg)	13
G.W.(kg)	14.5
Washing power	230W
High temp wash power	1000W
Max Water level(l)	13
40'HQ(pcs)	505



Stainless steel bucket
+
Stainless steel impeller

Function

- 60-80 degree high temp wash
- High power air drying function
- Stainless steel interior drum and
- washing wheel
- 24delay hours start, Auto shut off
- 10 Wash program options
- Child lock
- 6 Water level options

Mini Auto Washing Machine

3.0KG



XQB30-688W

Specification

Product size(mm)	345X395X610
Packing size(mm)	410X455X650
N.W.(kg)	13
G.W.(kg)	14.5
Washing power	230W
High temp wash power	1000W
Max Water level(l)	13
40'HQ(pcs)	505



Stainless steel bucket
+
Stainless steel impeller



PTC dryer



Rack (Option)

Function

- PTC dryer
- 60-80 degree high temp wash
- High power air drying function .
- Stainless steel interior drum and
- washing wheel
- 24delay hours start, Auto shut off
- 10 Wash program options
- Child lock
- 6 Water level options

3.0KG



XQB30-668L

Specification

Product size(mm)	345X395X610
Packing size(mm)	410X455X650
N.W.(kg)	13
G.W.(kg)	14.5
Washing power	230W
Max Water level(l)	13
40'HQ(pcs)	505



Stainless steel bucket
+
Plastic impeller

Function

- Blue light sterilization
- High power air drying function
- Plastic interior tub and washing wheel
- 24delay hours start, Auto shut off
- 10 Wash program options
- Child lock
- 6 Water level options

3.0KG



XQB30-668H

Specification

Product size(mm)	345X395X610
Packing size(mm)	410X455X650
N.W.(kg)	13
G.W.(kg)	14.5
Washing power	230W
Max Water level(l)	13
40'HQ(pcs)	505



Stainless steel bucket
+
Plastic impeller



Replaceable bucket

Function

- Blue light sterilization
- High power air drying function
- Plastic interior tub and washing wheel
- 24delay hours start, Auto shut off
- 10 Wash program options
- Child lock
- 6 Water level options
- TWO inner tubs, one is removable

5.2KG



XQB52-168

Specification

Product size(mm)	470X470X785
Packing size(mm)	510X510X800
N.W.(kg)	18
G.W.(kg)	20
40'HQ(pcs)	276

Function

- Plastic top lid
- 8 water level
- Air dry
- 10 Wash program
- Delay Start 1-24h
- Blue light
- Child lock

7.5KG



XQB75-A10

Specification

Product size(mm)	535X540X910
Packing size(mm)	560X560X925
N.W.(kg)	21.5
G.W.(kg)	24
40'HQ(pcs)	208

Function

- Plastic top lid
- 8 water level
- Air dry
- 10 Wash program
- Delay Start 1-24h
- Blue light
- Child lock

5.2KG



XQB52-168B

Specification

Product size(mm)	470X470X785
Packing size(mm)	510X510X800
N.W.(kg)	18
G.W.(kg)	20
40'HQ(pcs)	276

Function

- Plastic top lid
- 8 water level
- Air dry
- 10 Wash program
- Delay Start 1-24h
- Blue light
- Child lock

7.5KG



XQB75-A10B

Specification

Product size(mm)	535X540X910
Packing size(mm)	550X550X925
N.W.(kg)	25
G.W.(kg)	27
40'HQ(pcs)	208

Function

- Tempered glass top lid
- 8 water level
- Air dry
- 10 Wash program
- Delay Start 1-24h
- Child lock

Auto Washing Machine

9.0KG



XQB90-1915

Specification

Product size(mm)	582X590X945
Packing size(mm)	610X635X1020
N.W.(kg)	36
G.W.(kg)	38
40'HQ(pcs)	152

Function

- Tempered glass top lid
- 8 water level
- Air dry
- 10 Wash program
- Delay Start 1-24h
- Child lock

Auto Washing Machine

11.0KG



XQB110-1921

Specification

Product size(mm)	582X590X945
Packing size(mm)	610X635X1000
N.W.(kg)	31
G.W.(kg)	34
40'HQ(pcs)	152

Function

- Tempered glass top lid
- Touch control panel
- 10 water level
- Air dry
- 10 Wash program
- Delay Start 1-24h
- Child lock

9.0KG



XQB90-1916

Specification

Product size(mm)	522X535X930
Packing size(mm)	590X590X950
N.W.(kg)	26
G.W.(kg)	30
40'HQ(pcs)	200

Function

- Tempered glass top lid
- 8 water level
- Air dry
- 10 Wash program
- Delay Start 1-24h
- Blue light
- Child lock

11.0KG



XQB110-2022

Specification

Product size(mm)	577X587X944
Packing size(mm)	610X615X975
N.W.(kg)	28
G.W.(kg)	30
40'HQ(pcs)	150

Function

- Tempered glass top lid
- 8 water level
- Air dry
- 10 Wash program
- Delay Start 1-24h
- Blue light
- Child lock

Auto Washing Machine

12.0KG



XQB120-2201

Specification

Product size(mm)	612X629X975
Packing size(mm)	645X665X1005
N.W.(kg)	38
G.W.(kg)	40
40'HQ(pcs)	144

Function

- Tempered glass top lid
- 10 water level
- Air dry
- 10 Wash program
- Delay Start 1-24h
- Child lock

Auto Washing Machine

15.0KG



XQB150-2006

Specification

Product size(mm)	625X635X1000
Packing size(mm)	675X688X1025
N.W.(kg)	40
G.W.(kg)	42
40'HQ(pcs)	136

Function

- Tempered glass top lid
- 10 water level
- Air dry
- 10 Wash program
- Delay Start 1-24h
- Child lock

13.0KG



XQB130-2168

Specification

Product size(mm)	550X560X935
Packing size(mm)	590X590X970
N.W.(kg)	32
G.W.(kg)	34
40'HQ(pcs)	200

Function

- Tempered glass top lid
- 8 water level
- Air dry
- 10 Wash program
- Delay Start 1-24h
- Child lock

15.0KG



XQB150-2009

Specification

Product size(mm)	626X635X1000
Packing size(mm)	675X688X1025
N.W.(kg)	40
G.W.(kg)	42
40'HQ(pcs)	136

Function

- Tempered glass top lid
- 8 water level
- Air dry
- 10 Wash program
- Delay Start 1-24h
- Child lock

2 IN 1 Shoes washing machine

5.2KG



XQB52-168

Specification

Product size(mm)	470X470X785
Packing size(mm)	510X510X800
N.W.(kg)	18
G.W.(kg)	20
40'HQ(pcs)	276

Function

- Plastic top lid
- One key automatic laundry
- One key automatic shoe washing
- 12 programs optional
- Automatic fault detection
- No water detection
- Automatic power off function
- Cleaning bucket and air drying
- Electronic 8 speed water level choice
- The brush is removable

7.5KG



XQB75-A10

Specification

Product size(mm)	535X540X910
Packing size(mm)	560X560X925
N.W.(kg)	21.5
G.W.(kg)	24
40'HQ(pcs)	208

Function

- Plastic top lid
- One key automatic laundry
- One key automatic shoe washing
- 12 programs optional
- Automatic fault detection
- No water detection
- Automatic power off function
- Cleaning bucket and air drying
- Electronic 8 speed water level choice
- The brush is removable



Integral brush type



2 IN 1

BAOERMA 宝尔玛®

Twin Tub Washing Machine



Twin Tub Washing Machine

9.0KG/5.8KG



XPB90-2268S

Specification

Product size(mm)	730X430X853
Packing size(mm)	760X445X863
N.W.(kg)	16
G.W.(kg)	19
40'HQ(pcs)	224

Function

- Plastic top lid
- Plastic interior tub and washing impeller
- 2 washing program

Twin Tub Washing Machine

11.0KG/6.5KG



XPB110-2012S

Specification

Product size(mm)	770X440X940
Packing size(mm)	820X480X960
N.W.(kg)	22
G.W.(kg)	24
40'HQ(pcs)	164

Function

- Tempered glass top lid
- Plastic interior tub and washing impeller
- 2 washing program

12.0KG/6.5KG



XPB120-2011S

Specification

Product size(mm)	770X440X940
Packing size(mm)	820X480X960
N.W.(kg)	19
G.W.(kg)	22
40'HQ(pcs)	160

Function

- Plastic top lid
- Plastic interior tub and washing impeller
- 2 washing program

13.8KG/6.5KG



XPB138-2288S

Specification

Product size(mm)	810X480X985
Packing size(mm)	850X515X990
N.W.(kg)	22
G.W.(kg)	26
40'HQ(pcs)	140

Function

- Tempered glass top lid
- Plastic interior tub and washing impeller
- 2 washing program

Twin Tub Washing Machine

15.8KG/6.5KG



XPB158-2156S

Specification

Product size(mm)	860X530X1060
Packing size(mm)	900X545X1065
N.W.(kg)	28
G.W.(kg)	32
40'HQ(pcs)	136

Function

- Tempered glass top lid
- Plastic interior tub and washing impeller
- 2 washing program

15.8KG/6.5KG



XPB158-2158S

Specification

Product size(mm)	860X530X1025
Packing size(mm)	900X535X1030
N.W.(kg)	28
G.W.(kg)	32
40'HQ(pcs)	136

Function

- Tempered glass top lid
- Plastic interior tub and washing impeller
- 2 washing program

Twin Tub Washing Machine

16.0KG/6.8KG



XPB160-1608S

Specification

Product size(mm)	840X505X975
Packing size(mm)	875X535X980
N.W.(kg)	24.7
G.W.(kg)	28.9
40'HQ(pcs)	140

Function

- Tempered glass top lid
- Plastic interior tub and washing impeller
- 2 washing program

16.0KG/6.8KG



XPB160-1609S

Specification

Product size(mm)	840X505X975
Packing size(mm)	875X535X980
N.W.(kg)	24.7
G.W.(kg)	28.9
40'HQ(pcs)	140

Function

- Tempered glass top lid
- Plastic interior tub and washing impeller
- 2 washing program

Twin Tub Washing Machine

16.0KG/6.8KG

XPB160-1625S

Specification

Product size(mm)	840X505X975
Packing size(mm)	875X535X980
N.W.(kg)	24.7
G.W.(kg)	28.9
40'HQ(pcs)	130



Function

- Plastic top lid
- Plastic interior tub and washing impeller
- 2 washing program

Twin Tub Washing Machine

18.0KG/6.8KG

XPB180-1825S

Specification

Product size(mm)	861X517X1005
Packing size(mm)	906X546X1012
N.W.(kg)	26.2
G.W.(kg)	30.7
40'HQ(pcs)	130



Function

- Plastic top lid
- Plastic interior tub and washing impeller
- 2 washing program

16.0KG/6.8KG

XPB160-1625S

Specification

Product size(mm)	840X505X975
Packing size(mm)	875X535X980
N.W.(kg)	24.7
G.W.(kg)	28.9
40'HQ(pcs)	130



Function

- Plastic top lid
- Plastic interior tub and washing impeller
- 2 washing program

18.0KG/6.8KG

XPB180-1808S

Specification

Product size(mm)	861X517X1005
Packing size(mm)	906X546X1012
N.W.(kg)	26.2
G.W.(kg)	30.7
40'HQ(pcs)	130



Function

- Tempered glass top lid
- Plastic interior tub and washing impeller
- 2 washing program

Twin Tub Washing Machine

18.8KG/6.5KG



XPB188-2118S

Specification

Product size(mm)	890X540X1080
Packing size(mm)	930X550X1088
N.W.(kg)	30
G.W.(kg)	32
40'HQ(pcs)	96

Function

- Tempered glass top lid
- Plastic interior tub and washing impeller
- 2 washing program

Twin Tub Washing Machine

20.0KG/9.0KG



XPB200-2009S

Specification

Product size(mm)	956X526X1035
Packing size(mm)	1001X567X1042
N.W.(kg)	32.7
G.W.(kg)	37.6
40'HQ(pcs)	112

Function

- Tempered glass top lid
- Plastic interior tub and washing impeller
- 2 washing program

20.0KG/9.0KG



XPB200-2008S

Specification

Product size(mm)	956X526X1035
Packing size(mm)	1001X567X1042
N.W.(kg)	32.7
G.W.(kg)	37.6
40'HQ(pcs)	112

Function

- Tempered glass top lid
- Plastic interior tub and washing impeller
- 2 washing program

20.0KG/6.9KG



XPB200-2025S

Specification

Product size(mm)	956X526X1035
Packing size(mm)	1001X567X1042
N.W.(kg)	32.7
G.W.(kg)	37.6
40'HQ(pcs)	120

Function

- Plastic top lid
- Plastic interior tub and washing impeller
- 2 washing program

BAOERMA 宝尔玛®

INDUSTRIAL AIR COOLER



Industrial air cooler



FLYR-30 (Plastic top lid)

Voltage/Frequency:	AC220/50Hz
Power(W)	150
Product size(mm)	365X322X785
Packing size(mm)	420X375X775
N.W.(kg)	5.5
G.W.(kg)	6.7
Water tank capacity(L)	25
Airflow(m/H)	1300
40'HQ(pcs)	575



FLDY-30 (Plastic top lid)

Voltage/Frequency:	AC220/50Hz
Power(W)	50
Product size(mm)	285X240X580
Packing size(mm)	320X270X575
N.W.(kg)	4
G.W.(kg)	5
Water tank capacity(L)	12
Airflow(m/H)	1200
40'HQ(pcs)	1373

FLDY-30R (Plastic top lid) (Remote control)

Voltage/Frequency:	AC220/50Hz
Power(W)	50
Product size(mm)	285X240X580
Packing size(mm)	320X270X575
N.W.(kg)	4
G.W.(kg)	5
Water tank capacity(L)	12
Airflow(m/H)	1200
40'HQ(pcs)	1373

FLYR-30 (Glass top lid)

Voltage/Frequency:	AC220/50Hz
Power(W)	150
Product size(mm)	365X322X785
Packing size(mm)	420X375X775
N.W.(kg)	5.95
G.W.(kg)	7.2
Water tank capacity(L)	25
Airflow(m/H)	1300
40'HQ(pcs)	575

Industrial air cooler



FLYR-30R (Plastic top lid)
(Remote control)

Voltage/Frequency:	AC220/60Hz
Power(W)	150
Product size(mm)	365X322X785
Packing size(mm)	420X375X775
N.W.(kg)	5.5
G.W.(kg)	6.7
Water tank capacity(L)	25
Airflow(m/H)	1300
40'HQ(pcs)	575



FLYR-30R (Glass top lid)
(Remote control)

Voltage/Frequency:	AC220/60Hz
Power(W)	150
Product size(mm)	365X322X785
Packing size(mm)	420X375X775
N.W.(kg)	5.92
G.W.(kg)	7.2
Water tank capacity(L)	25
Airflow(m/H)	1300
40'HQ(pcs)	575



FLYR-40 (Glass top lid)

Voltage/Frequency:	AC220/60Hz
Power(W)	150
Product size(mm)	430X325X840
Packing size(mm)	485X375X800
N.W.(kg)	7.4
G.W.(kg)	8.8
Water tank capacity(L)	30
Airflow(m/H)	1800
40'HQ(pcs)	480

Industrial air cooler



FLYR-8000-121
(Plastic top lid)

Voltage/Frequency:	AC220/60Hz
Power(W)	280
Product size(mm)	620X420X1230
Packing size(mm)	655X465X1190
N.W.(kg)	14.5
G.W.(kg)	16.5
Water tank capacity(L)	80
Airflow(m/H)	5000
40'HQ(pcs)	193



FLYR-8000-121-1
(Glass top lid)

Voltage/Frequency:	AC220/60Hz
Power(W)	280
Product size(mm)	620X420X1230
Packing size(mm)	655X465X1190
N.W.(kg)	15.7
G.W.(kg)	17.5
Water tank capacity(L)	80
Airflow(m/H)	5000
40'HQ(pcs)	193



FLYR-80
(Plastic top lid ,metal bracket)

Voltage/Frequency:	AC220/60Hz
Power(W)	280
Product size(mm)	605X400X1120
Packing size(mm)	655X435X1085
N.W.(kg)	14.15
G.W.(kg)	16.15
Water tank capacity(L)	50
Airflow(m/H)	5000
40'HQ(pcs)	226



FLYR-40R (Plastic top lid)
(Remote control)

Voltage/Frequency:	AC220/60Hz
Power(W)	150
Product size(mm)	430X325X840
Packing size(mm)	485X375X800
N.W.(kg)	7.4
G.W.(kg)	8.8
Water tank capacity(L)	30
Airflow(m/H)	1800
40'HQ(pcs)	480



FLYR-5000-2
(High tank,metal bracket)

Voltage/Frequency:	AC220/60Hz
Power(W)	150
Product size(mm)	505X355X970
Packing size(mm)	550X395X940
N.W.(kg)	10.5
G.W.(kg)	11.85
Water tank capacity(L)	45
Airflow(m/H)	3400
40'HQ(pcs)	330



FLYR-5000-101
(Glass top lid)

Voltage/Frequency:	AC220/60Hz
Power(W)	150
Product size(mm)	510X360X1010
Packing size(mm)	545X390X980
N.W.(kg)	12
G.W.(kg)	13
Water tank capacity(L)	45
Airflow(m/H)	3400
40'HQ(pcs)	330



FLYR-80
(Glass top lid ,metal bracket)

Voltage/Frequency:	AC220/60Hz
Power(W)	280
Product size(mm)	605X435X1150
Packing size(mm)	655X435X1120
N.W.(kg)	14.9
G.W.(kg)	16.9
Water tank capacity(L)	50
Airflow(m/H)	5000
40'HQ(pcs)	226



FLYR-80R
(Plastic top lid ,metal bracket)

Voltage/Frequency:	AC220/60Hz
Power(W)	280
Product size(mm)	605X400X1120
Packing size(mm)	655X435X1085
N.W.(kg)	14.15
G.W.(kg)	16.4
Water tank capacity(L)	50
Airflow(m/H)	5000
40'HQ(pcs)	220



FLYR-80R
(Remote control)
(Glass top lid ,metal bracket)

Voltage/Frequency:	AC220/60Hz
Power(W)	280
Product size(mm)	605X435X1150
Packing size(mm)	655X435X1120
N.W.(kg)	14.4
G.W.(kg)	16.9
Water tank capacity(L)	50
Airflow(m/H)	5000
40'HQ(pcs)	220

Industrial air cooler



FLYR-120A
(Plastic top lid ,metal bracket)

Voltage/Frequency:	AC220/60Hz
Power(W)	280
Product size(mm)	840X490X1380
Packing size(mm)	870X530X1245
N.W.(kg)	16.5
G.W.(kg)	18.5
Water tank capacity(L)	100
Airflow(m/H)	8500
40'HQ(pcs)	120

FL4500-1BJ (Mechanic control)
FL4500-1BY (Remote control)

Voltage/Frequency:	AC220/50Hz
Power(W)	150
Product size(mm)	410X310X820
Packing size(mm)	440X335X810
N.W.(kg)	6.4
G.W.(kg)	8.8
Water tank capacity(L)	30
Airflow(m/H)	4500
40'HQ(pcs)	584

FL4500-BJ (Mechanic control)
FL4500-BY (Remote control)

Voltage/Frequency:	AC220/50Hz
Power(W)	150
Product size(mm)	410X310X920
Packing size(mm)	460X360X920
N.W.(kg)	7.3
G.W.(kg)	10.3
Water tank capacity(L)	35
Airflow(m/H)	4500
40'HQ(pcs)	462



FL5500-1BJ (Mechanic control)
FL5500-1BY (Remote control)

Voltage/Frequency:	AC220/50Hz
Power(W)	150
Product size(mm)	510X330X970
Packing size(mm)	565X370X960
N.W.(kg)	10.1
G.W.(kg)	12.5
Water tank capacity(L)	40
Airflow(m/H)	5500
40'HQ(pcs)	324



FL5500-BJ (Mechanic control)
FL5500-BY (Remote control)



FL7200-BJ (Mechanic control)
FL7200-BY (Remote control)

Voltage/Frequency:	AC220/50Hz
Power(W)	150
Product size(mm)	510X330X970
Packing size(mm)	565X370X960
N.W.(kg)	9.3
G.W.(kg)	12.8
Water tank capacity(L)	40
Airflow(m/H)	5500
40'HQ(pcs)	324

Industrial air cooler



FL9200-BJ (Mechanic control)
FL9200-BY (Remote control)

Voltage/Frequency:	AC220/50Hz
Power(W)	150
Product size(mm)	410X310X920
Packing size(mm)	460X360X920
N.W.(kg)	7.3
G.W.(kg)	10.3
Water tank capacity(L)	35
Airflow(m/H)	4500
40'HQ(pcs)	462



FL16000-SJ (Mechanic control)
FL16000-SY (Remote control)

Voltage/Frequency:	AC220/50Hz
Power(W)	280
Product size(mm)	610X410X1220
Packing size(mm)	664X450X1170
N.W.(kg)	15.0
G.W.(kg)	19.8
Water tank capacity(L)	60
Airflow(m/H)	9200
40'HQ(pcs)	190



FL28000-SJ (Mechanic control)
FL28000-SY (Remote control)

Voltage/Frequency:	AC220/50Hz
Power(W)	480
Product size(mm)	740X475X1330
Packing size(mm)	770X510X1280
N.W.(kg)	20.4
G.W.(kg)	26
Water tank capacity(L)	100
Airflow(m/H)	16000
40'HQ(pcs)	138

